



Code

AC950I

Model

MEAT 700 BLACK 115/60

cETLus certification: PENDING

Building characteristics

INSIDE covering			Mirror-polished S/S /
OUTSIDE covering			Black plastic-coated S/S /
Internal temp range			[+32°F ÷ +50°F]
Thickness of insulation: High density polyurethane foam (42 kg/m ³) without HCFC	in.	2.95	
Voltage V-Ph-Hz	115/1N/60		
Absorbed Power / Current	Kw .88 / Amps 9.1		
Includes:	n° 3 pairs of S/S shelf brackets - n° 3 S/S wire shelves 25.59"x20.87" - hook rail with 2 hooks rod (110.23 lbs)		
Electronic controller	TOUCHSCREEN		
HACCP Loggin Function	✓		
USB	✗		
WiFi/Bluetooth Connection	✓		
Key lock	✓		
Internal light	✓		
U.V. Lamps	✓		
Water condensing unit	Optional		
Net Weight	lbs.		370
		Packed	414.5
Cooling Capacity	ASHRAE	Watt	T. evap. +14°F / +131°F T.cond 630

Capillary / Thermostatic Valve			Cap.
Evaporator fan	Ø - Watt-Volt	1x9.84Ø-12W-115V	
Defrosting/heating	Watt	375W x 1/200W x 2	
Relative humidity	40% - 90%		
Internal storage capacity	lbs.	330.69	
Compressor	NEU6181U		
Condenser fan	Ø - Watt-Volt	1x7.87Ø-12W-115V	
Refrigerant	oz.	R290 GWP: 3 3.88	
Noise	Db(A)	52.1	

