

1832 N Glassell St · Orange, California 92865 1-888-MINIPAC · www.vac-smart.com

Item #_____ Quantity____ Project ____

MV 52 VacSmart[™] – Chamber Vacuum Sealer with Advanced <u>HACCP</u> Features



FEATURES

- Seamless stainless chamber 20" x 21"
- Height: 5" (Chamber) + 2.25" (Lid) = 7.25"
- Quick release seal bars at 21" length
- Transparent lid for operator viewing
- 304 stainless steel construction
- Shatterproof lid hinge design
- Full-color sealed LCD touch display
- Ethernet, USB, and Thermocouple connectivity
- TruVac[™] sensors for hold + vacuum pulse infusion
- Flippin' Tray for unique food shapes, sizes & liquids

SOFTWARE

- 6 speed keys
- 999+ product look-ups
- Selectable vacuum display in mbar or %
- HACCP Plan included at www.HACCP-Portal.com
- Fragile food protection with controlled air return

ADVANCED HACCP FEATURES

- E-data reporting with PDF file download
 - Operator, product, date/time, batch number
 - County of origin, supplier information, pH level, temperature
 - Immediate corrective action entry at vacuum machine
- Sanitation alerts
 - Food type change (i.e. beef fish beef)
 - 4-hour operation sanitation prompt
 - Air dry sanitation instructions
- ☐ Programmable label printer (optional)
 - Product name, packed date and use by date
 - Ingredients, product handling message, operator name
 - Sequential number, address, barcode, etc.

OPTIONS

- ☐ 208 volts, 50-60 Hz, 3-phase, 14 amps, 40 m³/h (MV 52 only)
- ☐ 220 volts, 50-60 Hz, single phase, 16 amps, 40 m³/h
- \square Inert gas kit $N_2/CO_2/AR$ injection (6/12 nozzles)
- ☐ Round seal for liquids + excess bag trimmer

MODELS

MV 52 VacSmart™

Left & Right Seal Bars

MV 52DV VacSmart™

Left & Right Seal Bars Two Vacuum Chambers













Features




1832 N Glassell St · Orange, California 92865 1-888-MINIPAC · www.vac-smart.com

MV 52 VacSmart™ - Chamber Vacuum Sealer with Advanced HACCP Features



ACCESSORIES

- ☐ 1. Direct thermal label printer (203 dpi)
- ☐ 2. Water-resistant flexible keyboard
- ☐ 3. Inkjet printer for HACCP reporting
- ☐ 4. K-Type needle temperature probe
- ☐ 5. Volume plates replaces Flippin' Tray
- ☐ 6. 2.5 quart aeration & food storage box



TECHNICAL SPECIFICATIONS

- Linux embedded operating system
- 5" LCD touch screen display, resistive type
- ARM Cortex A7 quad-core processor
- 1GB LPDDR2 RAM memory
- 8GB microSD storage
- WiFi & Bluetooth connectivity
- 10/100 Mbps Ethernet port
- Two USB 2.0 ports
- Two thermocouple ports

POWER

- VacSmart 52 20 m³/h Busch® vacuum pump 120 volts, 50-60 Hz, single phase, 18 amps
- VacSmart 52-DV 40 m³/h Busch® vacuum pump 208 volts, 50-60 Hz, 3-phase, 18 amps

SHIPPING

■ VacSmart 52

Shipping dimensions 30" x 34" x 51"H / 342 lbs

VacSmart 52-DV

Shipping dimensions 37" x 62" x 53"H / 692 lbs

DETAILS AND DIMENSIONS

- **24.5"** (620 mm)
- 51" (1296 mm)
- = **38.75**" (985 mm)
- **31.0"** (785 mm)
- = **36.25**" (920 mm)
- **50.5"** (1280 mm)

*VacSmart 52-DV



