









A compact vending solution that enables customers to enjoy natural chilled juice squeezed to order at any time.

- Incorporates the Z14C JUICING MACHINE, mounted on a tray with runners for easy handling and removal and includes compact chiller unit that can be removed easily for replacement or repair.
- The full squeezing process can be watched through an LED-illuminated window.
- Juice collection compartment is fitted with a window panel that remains closed automatically until the juice is delivered and locks again once the glass has been removed.
- Operating status information display
- · Alphanumeric system and illuminated icons.
- · 8 language options.
- · Serving counter.
- · Price of serving can be programmed in.
- · Fruit counter.
- · Rolling tally of accumulated credit.
- · Information on nature of any malfunction.
- **Electronic temperature control**. Refrigeration regulator that keeps the whole interior cold including the waste peel, to avoid attracting insects.
- Automatic self-clean programme which is set to run after certain number of juices have been delivered or a set length of time has elapsed. Connection to enable water to be drawn direct from the mains drinking water supply.
- Easy to clean. Fully removable parts.
- · Programmable rielda lock.
- Rear buffers ensure correct ventilation of cooling unit.
- · Back-lit front panel (led lights).
- Separate payment systems and programming zones, both housed in watertight compartments.
- · Accesible to wheelchair users.

Fruit Size

Medium-size cup kit Ø 2.16" - 2.95"

Large size cup kit Ø 2.75" - 3.54" (Optional)

Ideal

• For supermarkets and other retail outlets, hospitals, care homes, shopping centres, universities, schools, airports, sports centres and also for small and medium-size companies.

TECHNIQUE CHARACTERISTICS

Weight 496 lbs.

Power max, absorbed 706 W.

Capacity Feeder 55 lbs.

Autonomy 50-55 servings

Service times 20-26 seconds

Glasses Anti-static polystyrene glasses.

Glasses dispenser 115 mouth glasses units

Ø 2.75" - 2.79" (5 oz - 7.5 oz)

Refrigerant R134A

Load 9 oz.

Max. Inlet water pressure 6 bar.

Laterals stickers Front and side stickers standard.

Connectable Devices Optional: Coin Slot / Banknote Slot / Cash Less / Modem / Sound Mechanism (only

spanish). Consulting rates.

Voltage 110V-60Hz.

Security

• General Purpose Fuse. Thermal protection in juicing machine motor. Sensor detects incorrect positioning of juicing tray. Door sensor stops all moving parts when door opens.

Packaging